



MADE IN THE U.S.A.

S L I D E				S W I N G					OVERHEAD
<i>Res/Commercial</i>	<i>Com/Industrial</i>	<i>Com/Industrial</i>	<i>Com/Industrial</i>	<i>Single Home</i>	<i>Res/Commercial</i>	<i>Res/Commercial</i>	<i>Com/Industrial</i>	<i>Com/Industrial</i>	<i>Com/Industrial</i>
RAM 100 UL	RAM 1000 UL	RAM 5500 UL	RAM 5000 UL	RAM 30 UL	RAM 302 UL	RAM 300 UL	RAM 3000 UL	RAM 30-30 UL	RAM 2000 UL
20' @ 700 lbs. 1' / sec.	35' @ 1000 lbs. 1' / sec.	35' @ 1500 lbs. 1' / sec.	40' @ 1000 lbs. 1' / sec.	12' @ 400 lbs. 90° / 16 sec.	18' @ 600 lbs. 90° / 16 sec.	18' @ 800 lbs. 90° / 14 sec.	22' @ 800 lbs. 90° / 20 sec.	20' @ 3000 lbs. 90° / 16 sec.	20' @ 450 lbs. 90° / 14 sec.
Continuous	Continuous	Continuous	Continuous	30 cycles / hr	Continuous	Continuous	Continuous	Continuous	Continuous
1/2 Hp	1/2 Hp	3/4 Hp	1/2 Hp	1/2 Hp	1/2 Hp	1/2 Hp	1/2 Hp	3/4, 1 Hp	1/2 Hp
120 VAC.	120 VAC.	120 VAC.	120 VAC.	120 VAC.	120 VAC.	120 VAC.	120 VAC.	120, 220 VAC.	120 VAC.
4.5 amp	4.5 amp	8.5 amp	4.5 amp	5.2 amp	4.5 amp	4.5 amp	4.5 amp	4.5/8.5 amp	4.5 amp
50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.	50/60Hz.
-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F	-10°F to 160°F
H 22"	H 26"	H 27"	H 25"	H 20"	H 16 1/2"	H 27"	H 28 1/2"	H 27 1/2"	H 10"
L 14 1/2"	L 16"	L 16"	L 16 1/2"	L 13 1/2"	L 23"	L 16 1/2"	L 18"	L 17 1/2"	L 143"
W 15"	W 16 1/2"	W 16 1/2"	W 18 1/2"	W 13 1/2"	W 13 1/2"	W 20"	W 23"	W 23 1/2"	W 13"
110 lbs.	125 lbs.	135 lbs.	125 lbs.	75 lbs.	100 lbs.	110 lbs.	150 lbs.	200 lbs.	135 lbs.
Foot Pedal Release	Foot Pedal Release	Foot Pedal Release	Chain Release	Knob release	Hand Lever	Foot Pedal Release	Hand Lever	Knob release	Trolley Release
<p>BBS Battery Back-Up System</p> <ul style="list-style-type: none"> • Max. Capacity = 1000 lbs • Not available on the RAM 100 and the RAM 30 • On the RAM 300, the foot pedal is removed when the BBS is installed 				<p>RAM 5100 UL <i>MAX GATE SIZE & WEIGHT:</i> 40' @ 2000 lbs. <i>MOTOR:</i> 3/4 Hp 120VAC 8.5 amp 50/60Hz.</p> <p>RAM 5200 UL <i>MAX GATE SIZE & WEIGHT:</i> 40' @ 3000 lbs. <i>MOTOR:</i> 1 Hp 220VAC 4.5 amp 50/60Hz.</p>		<p>RAM 3100 UL <i>MAX GATE SIZE & WEIGHT:</i> 22' @ 1200 lbs. <i>MOTOR:</i> 3/4 Hp 120VAC 8.5 amp 50/60Hz.</p> <p>RAM 2100 UL <i>MAX GATE SIZE & WEIGHT:</i> 20' @ 700 lbs. <i>MOTOR:</i> 3/4 Hp 120VAC 8.5 amp 50/60Hz.</p>		<p>RAM 3200 UL <i>MAX GATE SIZE & WEIGHT:</i> 22' @ 1200 lbs. <i>MOTOR:</i> 1 Hp 220VAC 4.5 amp 50/60Hz.</p> <p>RAM 2200 UL <i>MAX GATE SIZE & WEIGHT:</i> 20' @ 700 lbs. <i>MOTOR:</i> 1 Hp 220VAC 4.5 amp 50/60Hz.</p>	

EASY INSTALLATION HEAVY DUTY RELIABLE LOW MAINTENANCE UP TO 10 YEAR WARRANTY
DISTRIBUTED BY ENGINEERED PARKING SYSTEMS www.epsinfo.com **(800) 377-4636**